

## DMD-004-001



Extension module 4 outputs DALI *broadcast*



<b>Maximum current</b>	4 lines DALI <i>broadcast</i> with max. 64 lights (power source <i>bus DALI</i> included)
<b>Power supply(tension)</b>	100-240VAC, frequency 50-60Hz
<b>Installation</b>	Rail DIN (larger 9 modules)
<b>Command system</b>	NO 100-240VAC or <i>bus</i> Domestia
<b>Power consumption</b>	Maximum 2W (outside of consumption <i>bus DALI</i> )
<b>Connecting terminals for power supply and outputs</b>	2 x 1.5mm <sup>2</sup> or 1 x 2.5mm <sup>2</sup>
<b>Connecting terminals for RS485 and bus DALI</b>	1 x 1.5mm <sup>2</sup>
<b>Protection</b>	Protection in case of short-circuit
<b>Pushbutton switch (mode stand alone)</b>	NO
<b>Pushbutton switch (mode <i>bus</i> Domestia)</b>	NO
<b>Temperature extremes</b>	-10°C to +45°C
<b>Maximum distance to the farthest PB switch</b>	50m in mode stand alone / 300m with le <i>bus</i> Domestia
<b>Weight</b>	306gr.
<b>Norms</b>	See page 2
<b>Packaging</b>	1Unit



# DOMESTIA